



TS10

Pinion C1.6-speed / Disc / Gates

Article	Inch	Frame size	ColorAmount
112020011	28"	Gents, 50 cm	black matt
112020012	28"	Gents, 55 cm	black mat
112020013	28"	Gents, 60 cm	black matt

Allgemein	Frame	Aluminium 6061, 28" Trekking Speed
	Head set	FSA, 1 1/8" semi-integrated
	Fork	28" Aluminium fork
	Shifting System	Pinion C1.6
	Derailleur	---
	Brakes	Shimano BR-MT200 (160 mm)
	Headlight	Busch&Müller Lumotec IQ-XS, 70 LUX
	Rear light	Busch&Müller, Toplight 2C Plus, LED
	Carrier	Racktime Light-it, without stiffener
	Saddle	Rabeneick VL3135 /w Rabeneick brand
	Seat post	Kalloy SP-DC1, patent, Aluminium, 31,6 mm, 300 mm
	Pedals	Marwi SP-823 Aluminium
	Kickstand	Pletscher Comp Zoom, rear stand
	Chainguard	---
Cockpit	Mudguard	SKS, Plastic
	Other	---
	Weight	14,3 kg
	Stem	Promax, DA-250, Aluminium, 1 1/8", rigid, 31,8 mm, quadruple clamping
Cockpit	Handlebars	Trekking, Aluminium, 640 mm
	Grips	Ergon GP1
	Shift lever	Pinion, twist shifter
	Brake lever	Shimano, Altus, 3-finger brake lever
Lauftrad/Reifen/Antrieb	Tires	Schwalbe Marathon Racer, 35-622
	Rims	Schürmann YAK19 Disc Aluminium hollow section rim
	Spokes	2 mm
	Front Hub	Shutter Precision SP PL-8, smooth-running hub dynamo
	Rear Hub	Shimano TX505
	Sprocket	Gates CDX belt pulley, 28 tooth
	Chain	Gates CDN drive belt
	Inner bearing	---
	Bottom bracket	Pinion Aluminium, 170 mm, with Gates CDX belt pulley 32 tooth
Lauftrad/Reifen/Antrieb	Gear ratio (f:r)	front: 32, rear: 28