



TC-E

Shimano Deore XT 10-speed / Bafang / 252Wh / Disc

Article	Inch	Frame size	ColorAmount
112020321	28"	Gents, 50 cm	black mat
112020322	28"	Gents, 55 cm	black mat
112020323	28"	Gents, 60 cm	black mat
112020326	28"	Ladies, 50 cm	black mat
112020327	28"	Ladies, 55 cm	black mat
112020331	28"	Gents, 50 cm	midnight mat
112020332	28"	Gents, 55 cm	midnight mat
112020333	28"	Gents, 60 cm	midnight mat
112020336	28"	Ladies, 50 cm	midnight mat
112020337	28"	Ladies, 55 cm	midnight mat

Allgemein	Frame	Aluminium 6061, 28" Trekking Comfort
	Head set	Chin Haur, 1 1/8" semi-integrated
	Fork	28" Aluminium fork
	Shifting System	Shimano Deore XT
	Derailleur	---
	Brakes	Shimano BR-MT200 (160 mm)
	Headlight	Herrmans MR8-E, 60 LUX
	Rear light	Busch&Müller, Carrier /w integrated rear light
	Carrier	Racktime Shine Evo Tour, without stiffener /w spring clamp
	Saddle	Selle Royal Milo Plus
	Seat post	Kalloy SP-DC1, patent, Aluminium, 31,6 mm, 300 mm
	Pedals	Aluminium, City/Trekking
	Kickstand	Pletscher Comp Zoom, rear stand
	Chainguard	Horn Catena 08
	Mudguard	SKS, Plastic
	Other	---
	Weight	19,8 kg

Cockpit	Stem	Humpert Ergotec, Octopus adjustable angle, safety level 4
	Handlebars	Humpert Ergotec, Ladytown, Aluminium, safety level 4
	Grips	Ergon GP1
	Shift lever	Shimano Deore
Lauftrad/Reifen/Antrieb	Brake lever	Shimano, Altus, 3-finger brake lever
	Tires	Schwalbe Energizer Active Plus, 47-622
	Rims	Schürmann YAK19 Disc Aluminium hollow section rim
	Spokes	2 mm
Lauftrad/Reifen/Antrieb	Front Hub	Shimano HB-TX505
	Rear Hub	Bafang rear-wheel motor
	Sprocket	Shimano HG50, 11-42 tooth
	Chain	KMC E10
	Inner bearing	Bafang torque sensor
	Bottom bracket	Lasco Aluminium, 170 mm
Lauftrad/Reifen/Antrieb	Gear ratio (f:r)	front: 42, rear: 11-42

E-Bike Antriebssystem

Motor
Bafang H400B
36 Volt, Rear-wheel motor
Output power 250 Watt
Display
Displayfunction via Bluetooth on Smartphone
Akku
Greenway Frame battery fully-integrated
Energy content: 252 Wh
Voltage: 36 Volt
Capacity: 7 Ah