



TS-E

Shimano Deore 10-speed / Bafang / 252Wh / Disc

Article	Inch	Frame size	Color
112120291	28"	Gents, 50 cm	black matt
112120292	28"	Gents, 55 cm	black matt
112120293	28"	Gents, 60 cm	black matt
112120296	28"	Ladies, 50 cm	black matt
112120297	28"	Ladies, 55 cm	black matt

General	Frame	Aluminum 6061, 28" Trekking Speed
	Head set	FSA, 1 1/8" semi-integrated
	Fork	28" aluminum fork
	Shifting System	Shimano Deore RD-M4120, 10-speed
	Derailleur	---
	Brakes	Shimano BR-MT200 (front 160 mm / rear 160 mm)
	Headlight	Herrmans MR8-E, 60 LUX
	Rear light	Herrmans, H-Trace
	Carrier	Racktime Light-it, IMM-system
	Saddle	Velo VL3135, with Rabeneick logo
	Seat post	Kalloy SP-DC1, patent, aluminum, 31,6 mm, 300 mm
	Pedals	Marwi SP-823
	Kickstand	Comp Zoom, rear kickstand
	Chainguard	Lasco chainguard
	Mudguard	SKS, plastic
	Other	permissible total weight 120 kg
	Weight	19,2 kg

Cockpit	Stem	Promax DA-250, aluminum
	Handlebars	Promax HB-3188, aluminum, 640 mm
	Grips	Ergon GP1, with clamp
	Shift lever	Shimano Deore SL-M4100, 10-speed
Wheels/Tires/Drivetrain	Brake lever	Shimano Altus, 3-finger brake lever
	Tires	Schwalbe Marathon Supreme, 37-622, reflex
	Rims	Schürmann YAK19 disc aluminum
	Spokes	Niro 2,0 mm, black
Wheels/Tires/Drivetrain	Front Hub	Shimano HB-TX505
	Rear Hub	Bafang G20 rear-wheel motor
	Sprocket	Shimano Deore CS-HG500, 11-42 teeth
	Chain	KMC E10 EPT
	Inner bearing	Bafang with torque sensor
	Bottom bracket	Lasco aluminum, 170 mm
	Gear ratio (f:r)	front 42, rear: 11-42

Drive System

Motor

Bafang H400B

36 Volt, rear-wheel motor

Output power 250 Watt

Display

displayfunction via bluetooth on smartphone

Battery

Greenway frame battery fully integrated

Energy content: 252 Wh

Voltage: 36 Volt

Capacity: 7 Ah

Technical changes and changes in equipment reserved, color deviations possible.