



TS5

Shimano Deore 30-speed / Disc

Article	Inch	Frame size	Color
112220041	28"	Gents, 50 cm	slate matt
112220042	28"	Gents, 55 cm	slate matt
112220043	28"	Gents, 60 cm	slate matt
112220046	28"	Ladies, 50 cm	slate matt
112220047	28"	Ladies, 55 cm	slate matt

Technical changes and changes in equipment reserved, color deviations possible.

General	Frame	Aluminum 6061, 28" Trekking Speed
	Head set	FSA, 1 1/8", a-head, semi-integrated
	Fork	28" aluminum
	Shifting System	Shimano Deore RD-T6000, 10-speed
	Derailleur	Shimano Deore FD-T6000, 3-speed
	Brakes	Radius BH-M960 (front 160 mm / rear 160 mm)
	Headlight	Jing Yi LED plastic, 70 LUX
	Rear light	AXA, Slim Steady LED
	Carrier	Racktime Light-it, with spring flap
	Saddle	Selle Royal Essenza
	Seat post	Promax, patent, aluminum, 31,6 mm, 300 mm
	Pedals	Marwi SP-823
	Kickstand	Rex, rear kickstand
	Chainguard	Shimano chainguard
Cockpit	Mudguard	SKS, plastic
	Other	maximum weight allowed 140 kg
	Weight	13,9 kg
	Stem	Promax DA-250, aluminum, 31,8 mm
	Handlebars	Promax HB-3188, aluminum, 640 mm
	Grips	Ergon GP1, with clamp
Wheels/Tires/Drivetrain	Shift lever	Shimano Deore SL-M6000, 3-/10-speed, with gear display
	Brake lever	Radius BH-M960, 3-finger brake lever
	Tires	Schwalbe Spicer Plus, 35-622, reflex
	Rims	Schürmann YAK19 Disc aluminum, 36 holes
	Spokes	2,0 mm, black
	Front Hub	Shutter Precision PL-8, hub dynamo, Centerlock, 36 holes
	Rear Hub	Joytech D762TSE, 36 holes
	Sprocket	Shimano CS-HG500, 10-speed, 11-34 teeth
	Chain	KMC X10
	Inner bearing	Shimano Deore SM-BB52, for Hollowtech II, BSA
	Bottom bracket	Shimano LX FC-T551, 170 mm, Hollowtech II, 48/36/26 teeth
	Gear ratio (f:r)	48/36/26 teeth : 11-34 teeth