



## TS5

Shimano Alfine 8-speed / Disc

| Article | Inch | Frame size    | ColorAmount |
|---------|------|---------------|-------------|
| 1190131 | 28"  | Gents, 50 cm  | slate matt  |
| 1190132 | 28"  | Gents, 55 cm  | slate matt  |
| 1190133 | 28"  | Gents, 60 cm  | slate matt  |
| 1190136 | 28"  | Ladies, 50 cm | slate matt  |
| 1190137 | 28"  | Ladies, 55 cm | slate matt  |

|                         |                         |                                                                  |
|-------------------------|-------------------------|------------------------------------------------------------------|
| Allgemein               | <b>Frame</b>            | Aluminium 6061, 28" Trekking Speed                               |
|                         | <b>Head set</b>         | FSA, 1 1/8" semi-integrated                                      |
|                         | <b>Fork</b>             | 28" Aluminium fork                                               |
|                         | <b>Shifting System</b>  |                                                                  |
|                         | <b>Derailleur</b>       | ---                                                              |
|                         | <b>Brakes</b>           | Shimano BR-MT200 (160 mm)                                        |
|                         | <b>Headlight</b>        | LED plastic, 70 LUX                                              |
|                         | <b>Rear light</b>       | Busch&Müller, Toplight 2C Plus, LED                              |
|                         | <b>Carrier</b>          | Racktime Light-it, stayless                                      |
|                         | <b>Saddle</b>           | Rabeneick VL3135, with Rabeneick Logo                            |
|                         | <b>Seat post</b>        | Kalloy SP-DC1, patent, Aluminium, 31,6 mm, 300 mm                |
|                         | <b>Pedals</b>           | Marwi SP-823 Aluminium                                           |
|                         | <b>Kickstand</b>        | Pletscher Comp Zoom, rear kickstand                              |
|                         | <b>Chainguard</b>       | ---                                                              |
|                         | <b>Mudguard</b>         | SKS, plastic                                                     |
| Cockpit                 | <b>Other</b>            | ---                                                              |
|                         | <b>Weight</b>           | 13,9 kg                                                          |
|                         | <b>Stem</b>             | Promax, DA-250, Aluminium, 1 1/8", stiff, 31,8 mm, 4-times clamp |
|                         | <b>Handlebars</b>       | Trekking, Aluminium, 640 mm                                      |
|                         | <b>Grips</b>            | Ergon GP1                                                        |
| Lauftrad/Reifen/Antrieb | <b>Shift lever</b>      | Shimano Alfine                                                   |
|                         | <b>Brake lever</b>      | Shimano, Altus, brake lever                                      |
|                         | <b>Tires</b>            | Schwalbe Marathon Racer, 35-622                                  |
|                         | <b>Rims</b>             | Schürmann YAK19 Disc Aluminium double wall rim                   |
|                         | <b>Spokes</b>           | 2 mm                                                             |
|                         | <b>Front Hub</b>        | Shutter Precision PL-8, Light Hub Dynamo                         |
|                         | <b>Rear Hub</b>         | Shimano Alfine 8-speed free wheel hub                            |
|                         | <b>Sprocket</b>         | Shimano 20 teeth                                                 |
|                         | <b>Chain</b>            | KMC Z-610RB, anti rust                                           |
|                         | <b>Inner bearing</b>    | Thun Topaz, 4-square                                             |
|                         | <b>Bottom bracket</b>   | Lasco Aluminium, 170 mm, 42 teeth                                |
|                         | <b>Gear ratio (f:r)</b> | 42 teeth : 20 teeth                                              |