



TS-E

Shimano Deore XT 10-speed / Bafang / 252Wh / Disc

Article	Inch	Frame size	ColorAmount
1190401	28"	Gents, 50 cm	black matt
1190402	28"	Gents, 55 cm	black matt
1190403	28"	Gents, 60 cm	black matt
1190405	28"	Ladies, 50 cm	black matt
1190406	28"	Ladies, 55 cm	black matt
1190431	28"	Gents, 50 cm	slate matt
1190432	28"	Gents, 55 cm	slate matt
1190433	28"	Gents, 60 cm	slate matt
1190435	28"	Ladies, 50 cm	slate matt
1190436	28"	Ladies, 55 cm	slate matt

Allgemein	Frame	Aluminium 6061, 28" Trekking Speed
	Head set	FSA, 1 1/8" semi-integrated
	Fork	28" Aluminium fork
	Shifting System	Shimano Deore XT
	Derailleur	---
	Brakes	Shimano BR-MT200 (160 mm)
	Headlight	Busch&Müller Lumotec Avy, 40 LUX
	Rear light	Busch&Müller, Toplight 2C Plus, LED
	Carrier	Racktime Light-it, stayless
	Saddle	Rabeneick VL3135, with Rabeneick Logo
	Seat post	Kalloy SP-DC1, patent, Aluminium, 31,6 mm, 300 mm
	Pedals	Marwi SP-823 Aluminium
	Kickstand	Pletscher Comp Zoom, rear kickstand
	Chainguard	Lasco chain protectionring
	Mudguard	SKS, plastic
	Other	---
	Weight	ca.19,4 kg

Cockpit	Stem	Promax, DA-250, Aluminium, 1 1/8", stiff, 31,8 mm, 4-times clamp
	Handlebars	Trekking, Aluminium, 640 mm
	Grips	Ergon GP1
	Shift lever	Shimano Deore
LaufRad/Reifen/Antrieb	Brake lever	Shimano, Altus, brake lever
	Tires	Schwalbe Marathon Supreme, 37-622
	Rims	Schürmann YAK19 Disc Aluminium double wall rim
	Spokes	2 mm
LaufRad/Reifen/Antrieb	Front Hub	Shimano Deore
	Rear Hub	Bafang backwheelmotor
	Sprocket	Shimano HG50, 11-42 teeth
	Chain	KMC E10
	Inner bearing	Bafang torque sensor
	Bottom bracket	Lasco Aluminium, 170 mm
LaufRad/Reifen/Antrieb	Gear ratio (f:r)	42 teeth : 11-42 teeth

E-Bike Antriebssystem

Motor
Bafang H400B
36 Volt, backwheelmotor
Output power 250 Watt
Display
Displayfunction via Bluetooth on Smartphone
Akku
DRN New Energy framebattery full-integrated
Energy content: 252 Wh
Voltage: 36 Volt
Capacity: 7 Ah